



 SK-(SENSOR#) + PLE  
Straight Wire Sensor

# SENSOR DESCRIPTIONS

Each Sensor **MUST** have a PLE (Straight) or CLE (Coiled) Suffix


 SK-(SENSOR#) + CLE  
Coiled Sensor

**SK-902\***



Square Sensor– 1"W x 1"L x 1/2"H

**SK-904**



Rectangular Sensor– 1"W x 2"L x 1/4"H

**SK-914**



Waffle Sensor– 1-1/4"W x 3-3/8"L x 1/2"H

**SK-915\***




Mini Slim-Line Sensor– 1" dia. x 5/8"H

**SK-917**




Mini Slim-Line Sensor w/Hole– 1" dia. x 5/8"H

**SK-926**




USB Type B Sensor– 3/8"W x 1-1/4"L x 3/8"H

**SK-928**




Allows USB Pass-Through  
USB Port Sensor– 13/16"W x 2"L x 7/16"H

**SK-929**




Mini USB Sensor– 5/16"W x 3/4"L x 1/8"H

**SK-931**




RCA Jack Sensor– 1-1/2"W x 9/16"L x 5/8"H

**SK-932**




Mouse Sensor– 11/16"W x 1"L x 1/2"H

**SK-934**




Allows Mini USB Pass-Through  
Mini USB Sensor– 3/4"W x 1-3/16"L x 7/16"H

**SK-938**



Non Pass-Through  
USB Port Sensor– 13/16"W x 1-1/2"L x 7/16"H

**SK-940**




Rect. Sensor w/Micro Switch– 1"W x 2"L x 1/4"H

**SK-943\***




Tie Sensor– 1"W x 1-1/2"L x 1"H

**SK-944**



RJ45 (Ethernet) Sensor– 7/16"W x 7/8"L x 5/16"H

**SK-946**



VGA Port Sensor– 1-5/8"W x 2"L x 5/8"H

**SK-953**



approx. 6-1/2" loop  
Collar Lasso Sensor– 1-1/4" W x 3/4"L x 7/8"H

**SK-955\***



Slim-Line Sensor– 1-1/4" dia. x 13/16"H

**SK-956**




Slim-Line Sensor w/Hole– 1-1/4" dia. x 13/16"H

**SK-961\***



Ant Sensor– 7/16"W x 11/16"L x 9/16"H

**SK-968**




Telephone Jack Sensor– 3/16"W x 3/4"L x 1/4"H

**SK-990**




See Page 9 for Bendable Sensor Labels  
Bendable Label Sensor– 15/16"W x 1-1/4"L x 9/16"H

**SK-994T**




See Page 9 for Bendable Sensor Labels  
Top Pull Bendable Label Sensor– 15/16"W x 7/8"L x 5/8"H

**SK-995**




Requires Detachable Cable (see page 9)  
Detachable Slim-Line Sensor– 1-1/4" dia. x 3/4"H

**SK-997**



Available in Right Angle Version  
Pneumatic (Air Tool) Sensor– 1/2" dia. x 1"H

**SKD-6168**



Dual Sensor– (Ant To Telephone Jack)

**SKD-0453**



Dual Sensor– (Rectangular To Collar Lasso)

**\* These Sensors Have a Tie-Wrap Option Built-In.**

Please specify, by using a suffix after the sensor number, whether you wish coiled wire (CLE) or straight wire (PLE). Sensors are available in white, grey and black (sold in black unless otherwise stated). Wires are approximately 6 feet in length (straight or stretched).

**If you don't see it, we'll build it!**



**Se-Kure Controls,® Inc.**

On the Web: [www.se-kure.com](http://www.se-kure.com)  
E-Mail: [info@se-kure.com](mailto:info@se-kure.com)

3714 Runge Street • Franklin Park, IL 60131 • 1-(800) 322-2435 • (847) 288-1111 • Fax: (847) 288-9999